

# Rubiomonocoat SEALER 707

## DESCRIPTION:

Rubio Monocoat Sealer 707 is a specially formulated waterbased wood finish based on a hybrid polyurethane polymer dispersion. RMC Sealer 707 has been developed for sealing charred wood finishes to prevent release of carbon. The product seriously reinforces the brittle surfaces and highly increases the handling.

## SPECIFIC FEATURES:

- Highly durable
- Non yellowing
- Excellent resistance against water
- VOC free
- Nearly odorless
- Sealer dries out nearly invisible
- Very low foaming

## APPLICATION:

RMC Sealer 707 is preferably applied by spray/curtain coater in two applications/layers. One layer is possible however care must be taken that the wood boards are properly saturated in that case. Application by brush is possible, but not preferable due to possible damaging of the charred and brittle boards.

## REMARK:

- RMC Sealer 707 can be used on both indoor and outdoor wood.
- RMC Sealer 707 can be applied on Shou Sugi Ban charred wood.

## CONSUMPTION:

Approx. 150 ml/m<sup>2</sup> per layer. Normally 2 layers are sufficient, a third layer is sometimes necessary.  
*These usages are merely indicative. It is always recommended to make a sample in order to calculate the exact usage.*

## TECHNICAL CHARACTERISTICS:

Physical state at 20 °C: liquid

Color: white

Odor: characteristic

Flame point: > 100 °C

Specific density (kg/l): 1 kg/L

## STORAGE:

The product can be stored for 12 months in a dry environment and in its original packaging.  
Store in frost-free conditions.

## PACKAGING:

Can 1 L and 5 L

PROVIDED BY:

DISCLAIMER: It is the responsibility of the user to determine through own testing whether the product is suited for its chosen application. Muylle Facon NV is not liable for any resultant damage. The above information may be subject to amendments, which will be published in revised versions of the technical sheet. We waive all responsibility for unsatisfactory results that are due to causes unrelated to the quality of the product. This technical information has been collected on the basis of current information and knowledge. The most recent technical sheets can be requested or are available on the website.



Consult the safety sheet before use.  
Date TDS: 16/12/16

**MUYLLE FACON**

MADE IN BELGIUM by N.V. MUYLLE - FACON S.A.  
Ambachtenstraat 58 - B-8870 Izegem (Industriezone Abele)  
Tel. +32 (0)51 30 80 54 - Fax + 32 (0)51 30 99 78 - HRK 1823  
info@muyllefacon.be - [www.rubimonocoat.com](http://www.rubimonocoat.com)

