



Exterior Wood Cleaner was developed for the thorough cleaning of all types of wood surfaces, such as terraces, garden furniture, fences, canopies, doors and windows. The product quickly and efficiently dissolves dirt, thereby assuring an optimal surface for subsequent treatment.

- **Effective removal of dirt and grease**
- **Prepares the surface for subsequent treatment**
- **Easy to use**



Application area

For new and old wood. Ideal for surfaces such as garden furniture, terraces, fences, canopies, window frames, doors and carports. Can also be used on masonry and concrete.

Work description

Preparation	<p>Treatment should only be performed in dry weather conditions. Avoid direct sunlight and excessive heat. Remove all loose foliage, branches, etc. and then soak the wood with water. Use a garden hose if possible.</p> <p>Always remember to test on a less visible spot to check the compatibility of the surface with the product.</p>
Treatment	<p>Mix Exterior Wood Cleaner with water in a ratio of 1:2 - 1:10, depending on how dirty the wood is. Apply the cleaner in an even coat, using a brush or spray nozzle. Leave the cleaner to work for five minutes. Scrub in the longitudinal direction of the wood grain using a stiff-bristled brush, until the surface is clean. We recommend WOCA Silicium Carbide Brush or Outdoor Scrubbing Brush for the best results. Repeat if necessary. Rinse the surface with plenty of water and leave the wood to dry for a minimum of 24 hours.</p>
Please note	<p>Exterior Wood Cleaner can also be used on masonry and concrete.</p>

Drying time

Drying time	1-2 days at 20°C
-------------	------------------



Technical data

Declaration	Less than 5%: cationic surfactants, non-ionic surfactants.
Density	1-1.1 g/ml
pH-value	11
Shelf life	36M
Application Temperature	+15-30°C
Coverage	Approx. 100 m ² /L, depending on wood type and surface
Mixing ratio	1:2 - 1:10, depending on how dirty the wood is.
Storage	+10-25°C. Keep out of reach of children. Do not expose to heat (e.g. sunlight). Store frost-free during winter and cool during summer.
Packaging	1 L - 2.5 L

Maintenance and related products

Related products	Exterior Wood Oil, #6179XX
------------------	----------------------------

Contact

WOCA Denmark A/S
Tvæervej 6
DK - 6640 Lunderskov
T +45 9958 5600
info@wocadenmark.com
wocadenmark.com

This information is based on extensive laboratory testing and practical experience. Because the conditions under which the product is used are often beyond the control of WOCA Denmark, we can only guarantee the quality of the actual product. WOCA Denmark A/S accepts no liability for incorrect use and handling of the product. In principle, this product can be considered an intermediate product, as results depend on construction, the nature of the surface, pre-treatment, temperature, air humidity, application etc. WOCA Denmark A/S reserves the right to change the product and the stated information without notice. This label/product description replaces all previous versions.