



SAFETY DATA SHEET
ACCORDING TO 1907/2006/EC, ARTICLE 31
HARD WAX OIL

HAZARDS IDENTIFICATIONS

Classification -

1999/45 EC Main hazards

Xn;R65 R10-66

Flammable. Harmful: may cause lung damage if swallowed. Repeated exposure may cause skin dryness or cracking

Other hazards

The product is classified in accordance with 67/548/EEC

COMPOSITION/ INFORMATION ON INGREDIENTS

Mixtures

67/548/EEC / 1999/45/EC

Chemical name	Index No.	CAS No.	EINECS No.	Reach Registration number	Conc (%w/w)	Classification
Deamoris white spirit		64742-48-9	265-150-3		50-60%	Xn;R65 R10-66

Additional information: The product does not require a hazard warning label in accordance with EC Directives.

FIRST AID MEASURES

Inhalation Move the exposed person to fresh air. Seek medical attention.

Eye contact Rinse immediately with plenty of water for 15 minutes holding the eyelids open. Seek medical attention.

Skin contact Wash off immediately with plenty of soap and water. Remove contaminated clothing.

Ingestion DO NOT INDUCE VOMITING. Drink 1 or 2 glasses of water. Seek medical attention.

FIREFIGHTING MEASURESExtinguishing media Use extinguishing media appropriate to the surrounding fire conditions.
Do NOT use water jet.

Advice for firefighters Wear: Self-contained breathing apparatus.

ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation of the working area. Keep personnel away from spill. Evacuate personnel to a safe area. Eliminate all sources of ignition.

Environmental precautions

Do not allow product to enter drains.

Methods and material for containment and cleaning up

Clean spillage area thoroughly with plenty of water. Absorb with inert, absorbent material. Transfer to suitable, labelled containers for disposal.

HANDLING AND STORAGE

Precautions for safe handling

Wear suitable equipment. Do not breathe gas/fumes/vapour/spray. Use in a well ventilated area. Vapours are heavier than air. Avoid contact with eyes and skin.

Conditions for safe storage, including any incompatibilities

Keep in cool, dry, well ventilated area. Keep containers tightly closed.

EXPOSURE CONTROLS/ PERSONAL PROTECTION

Appropriate engineering controls

Ensure adequate ventilation of the working area

Individual protection

Avoid contact with eyes and skin. Adopt best manual handling considerations when handling, carrying and dispensing. Apron (plastic or rubber). Rubber boots

Eye/ Face protection

Approved safety goggles. Avoid contact with eye.

Skin and hand protection

Chemical resistant gloves. (PVC)

Respiratory protection

Wear suitable respiratory equipment. Self-contained breathing apparatus.

PHYSICAL AND CHEMICAL

State Liquid

Colour Amber

Odour Mild

Flash Point 43

STABILITY AND REACTIVITY

Chemical stability

Stable under normal conditions

Possibility of hazardous reactions

Oxidising agents. Acids

Conditions to avoid

Heat, sparks and open flames

Hazardous decomposition products

Carbon oxides. Nitrogen oxides

TOXICOLOGICAL INFORMATION

Acute toxicity

Headache, nausea and vomiting in severe cases, may cause loss of consciousness. Harmful if absorbed through the skin.

Skin corrosion/ Irritation

May cause irritation to skin.

Repeated or prolonged exposure

Prolonged or repeated exposure may cause irritation to skin and mucous membranes. Repeated or prolonged exposure may cause dermatitis.

ECOLOGICAL INFORMATION

Toxicity

No data is available on this product

DISPOSAL CONSIDERATIONS

General informations

Can be incinerated if in compliance with local and national regulations.

Disposal of packing

Dispose of in compliance with all local and national regulations.

Empty containers can be sent for disposal or recycling

TRANSPORT INFORMATION

Hazard pictograms



UN Number

UN1263

UN proper shipping name

PAINTED RELATED MATERIAL

Transport hazard class(es)

ADR/RID

3

Subsidiary risk

-

IMDG

3

Subsidiary risk

-

IATA

3

Subsidiary risk

-

Packing group

III

Environmental hazards

No

Marine pollutant

No

ADR/RID Hazard ID

30

ADR/RID Tunnel category

(D/E)

IMDG

F-E-S-E

Packing instruction

310

Maximum quantity

220L



REGULATORY INFORMATION

Symbols

The product is classified in accordance with 67/548/EEC

Xn: Harmful



Risk phrases

R10 - Flammable

R65 - Harmful: may cause lung damage if swallowed

R66 - Repeated exposure may cause skin dryness or cracking

Safety phrases

S62 - If swallowed, do not induce vomiting: seek medical advice and show this container or label.

OTHER INFORMATION

Revision

This document differs from the previous version in the following areas:
14 - adr/rid.

Text of risk phrases in section 3

R10 - Flammable

R65 - Harmful: may cause lung damage if swallowed

R66 - Repeated exposure may cause skin dryness or cracking

Product subcategory

Interior/exterior trim varnished and wood stains, including opaque woodstains - 400 g/l

General information

S1/2 - Keep locked up and out of the reach of children.

S13 - Keep away from food, drink and animal feeding stuffs.

S7/9 - Keep container tightly closed and in a well-ventilated space.

S26 - In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

S37/39 - Wear suitable gloves and eye/face protection

Further information

The information supplied in this Safety Data Sheet is designed only as guidance for the safe use, storage and handling of the product. This information is correct to the best of our knowledge and belief at the date of publication however no guarantee is made to its accuracy. This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any other process. The product is classified in accordance with 67/548/EEC.

