



HOTwood Clear Pine Open Line QuickClip® Acoustic SV1QC-A-10



Interval of 10mm

Acoustic ceiling





Suspension system with adjustable fixation to the ceiling

Air gap from 100mm to 600mm



System with frame screws

Air gap from 25mm to 100mm



Technical specifications

Board dimensions	20mm (thickness) x 65mm (width) x ± 3000 mm/+
Aluminium joist dimensions	24mm (thickness) x 63mm (width)
Total thickness	50mm (profile 20mm + clip 6mm + aluminium joist 24mm)
Gap between boards	10mm
Centre distance of boards	75mm
Wood variety	HOTwood Clear Pine (thermally treated Clear Pine)
Certification	PEFC
Durability class	1 (CATAS certificate available upon request)
Moisture content	4-6%
Bending strength	81,9N/mm ²
Modulus of elasticity	15,68kN/mm ²
Density	415.5kg/m ³
Width shrinkage for EMC 35-65%	0.39%

Acoustic specifications

High sound absorption thanks to the 602 - 25mm Isover Climliner Slab, a solid, glass wool panel, clad on one side with a sheet of reinforced black glass

Acoustics tests to be conducted

Installation system

QuickClip® cladding is delivered with the Grad® installation system. Reverse side has a 5.8mm x 11.8mm groove into which Grad® clips (in polyoxymethylene, a plastic derivative) slot perfectly. All plastic clips are pre-installed on a black painted aluminium rail. Their centre distance is always adjusted to suit the profile.

Installation instructions, see https://youtu.be/ooUzzRAAJ_Q