





HOTwood pine
Cubus QuickClip® Acoustic
CBQC-A-38

Interval of 38mm

Acoustic ceiling





Suspension system with adjustable fixation to the ceiling
Air gap from 100mm to 600mm



System with frame screws

Air gap from 25mm to 100mm





Technical specifications

Board dimensions	42mm (thickness) x 42mm (width) x ± 1500 mm/+
Aluminium joist dimensions	24mm (thickness) x 63mm (width)
Total thickness	72mm (profile 42mm + clip 6mm + aluminium joist 24mm)
Gap between boards	38mm
Centre distance of boards	80mm
Wood variety	HOTwood pine (thermally modified pine)
Certification	PEFC
Durability class	1-2 (CATAS certificate available upon request)
Moisture content	4-6%
Bending strength	17.41N/mm ²
Modulus of elasticity	3.44kN/mm ²
Density	415.5kg/m ³
Width shrinkage for EMC 35-65%	0.39%

Acoustic specifications

High sound absorption thanks to the 602 - 25mm Isover Climliner Slab, a solid, glass wool panel, clad on one side with a sheet of reinforced black glass

Sound absorption Class C, calculated according to the ISO 11654 standard



Installation system

QuickClip® cladding is delivered with the Grad® installation system. Reverse side has a 5.8mm x 11.8mm groove into which Grad® clips (in polyoxymethylene, a plastic derivative) slot perfectly. All plastic clips are pre-installed on a black painted aluminium rail. Their centre distance is always adjusted to suit the profile.

Installation instructions, see https://youtu.be/ooUzzRAAJ_Q